

1970	1971	1972	1973	1974	1975	1976	1977	1978	1979	1980	1981	1982	1983	1984	1985	1986	1987	1988	1989	1990	1991	1992	1993	1994	1995	1996	1997	1998	1999	2000	2001	2002	2003	2004	2005	2006	2007	2008	2009	2010	2011	2012	2013	2014	2015	2016	2017	2018	2019	2020	2021	2022	2023	2024	2025	2026	2027	2028	2029	2030	2031	2032	2033	2034	2035	2036	2037	2038	2039	2040	2041	2042	2043	2044	2045	2046	2047	2048	2049	2050	2051	2052	2053	2054	2055	2056	2057	2058	2059	2060	2061	2062	2063	2064	2065	2066	2067	2068	2069	2070	2071	2072	2073	2074	2075	2076	2077	2078	2079	2080	2081	2082	2083	2084	2085	2086	2087	2088	2089	2090	2091	2092	2093	2094	2095	2096	2097	2098	2099	2100	2101	2102	2103	2104	2105	2106	2107	2108	2109	2110	2111	2112	2113	2114	2115	2116	2117	2118	2119	2120	2121	2122	2123	2124	2125	2126	2127	2128	2129	2130	2131	2132	2133	2134	2135	2136	2137	2138	2139	2140	2141	2142	2143	2144	2145	2146	2147	2148	2149	2150	2151	2152	2153	2154	2155	2156	2157	2158	2159	2160	2161	2162	2163	2164	2165	2166	2167	2168	2169	2170	2171	2172	2173	2174	2175	2176	2177	2178	2179	2180	2181	2182	2183	2184	2185	2186	2187	2188	2189	2190	2191	2192	2193	2194	2195	2196	2197	2198	2199	2200	2201	2202	2203	2204	2205	2206	2207	2208	2209	2210	2211	2212	2213	2214	2215	2216	2217	2218	2219	2220	2221	2222	2223	2224	2225	2226	2227	2228	2229	2230	2231	2232	2233	2234	2235	2236	2237	2238	2239	2240	2241	2242	2243	2244	2245	2246	2247	2248	2249	2250	2251	2252	2253	2254	2255	2256	2257	2258	2259	2260	2261	2262	2263	2264	2265	2266	2267	2268	2269	2270	2271	2272	2273	2274	2275	2276	2277	2278	2279	2280	2281	2282	2283	2284	2285	2286	2287	2288	2289	2290	2291	2292	2293	2294	2295	2296	2297	2298	2299	2300	2301	2302	2303	2304	2305	2306	2307	2308	2309	2310	2311	2312	2313	2314	2315	2316	2317	2318	2319	2320	2321	2322	2323	2324	2325	2326	2327	2328	2329	2330	2331	2332	2333	2334	2335	2336	2337	2338	2339	2340	2341	2342	2343	2344	2345	2346	2347	2348	2349	2350	2351	2352	2353	2354	2355	2356	2357	2358	2359	2360	2361	2362	2363	2364	2365	2366	2367	2368	2369	2370	2371	2372	2373	2374	2375	2376	2377	2378</
------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	--------

**APPLICANT:** Saburou Ikeda

# Saburou Ikeda

**FOR:**

# APPARATUS AND METHOD FOR ESTABLISHING DIAL-UP BRANCH CONNECTIONS TO INTERNET SERVICE PROVIDERS

**DOCKET NO.:**

**NE-1018-US/KM**

TITLE OF THE INVENTION**APPARATUS AND METHOD FOR ESTABLISHING DIAL-UP BRANCH  
CONNECTIONS TO INTERNET SERVICE PROVIDERS**BACKGROUND OF THE INVENTIONField of the Invention

The present invention relates generally to dial-up connection to internet service providers, and more particularly to an apparatus and method for accessing multiple internet service providers at low cost by using dial-up IP (internet protocol) service.

Description of the Related Art

Dial-up IP service allows subscribed user terminals to establish dial-up connections to internet service providers through a public switched telephone network. To provide this service, internet service providers are connected to the public switched telephone network through dial-up lines that are leased from the network provider and assigned phone numbers as in the case of most telephone subscribers. The total number of such leased lines is less than the number of subscribed users in order to establish a reasonable balance between operating cost and profit. However, communication traffic offered to the leased lines as well as to the public switched network will increase significantly when flat rate service is introduced for dial-up connections. In addition, since dial-up users are connected to internet service providers in a one-to-one correspondence, it is necessary for the internet service providers to install equipment in the public switched network that can communicate with the subscribers' modems with perfect compatibility. Further, due to communication protocols and transmission speeds of the installed

1 equipment, the leased lines must be grouped according to such different  
2 implementation parameters and reassigned new phone numbers (i.e., pilot  
3 numbers) to maintain compatibility. The subscribers must be informed of the  
4 reassigned phone numbers to update their internet access number. Since  
5 different pilot numbers are used for different groups of leased lines, a split  
6 loss occurs in the utilization efficiency of transmission medium. This is  
7 particularly true of ADSL (asymmetric digital subscriber line) since the  
8 number of lines leased for this service is significantly limited.

9 SUMMARY OF THE INVENTION

10 It is therefore an object of the present invention to provide an  
11 apparatus and method for accessing multiple internet service providers with  
12 low access charges without generating an extra load on the traffic of public  
13 switched network.

14 According to a first aspect, the present invention provides a connection  
15 apparatus for a public network switching system which serves user terminals.  
16 The apparatus comprises a switching unit having a plurality of diverging ports  
17 connected to the switching system and a plurality of converging ports adapted  
18 for connection to a plurality of internet lines, and a control unit for receiving a  
19 request signal of one of the user terminals and establishing in the switching  
20 unit a set of branch connections between one of the diverging ports and ones of  
21 the converging ports corresponding to the internet lines specified by the  
22 request signal, the one diverging port being connected through a connection to  
23 the one user terminal established in the switching system. The switching  
24 system may be configured to serve a plurality of internet lines, and the control  
25 unit is configured to request the switching system to establish a plurality of

1 connections between the converging ports and the plurality of internet lines.

2 Each of the converging ports may include a multiplexer for multiplexing  
3 a plurality of user signals into a signal for transmission to one of the internet  
4 lines and a demultiplexer for demultiplexing a signal from the internet line into  
5 a plurality of signals for application to the diverging ports.

6 According to a second aspect, the present invention provides a  
7 connection apparatus for a public network switching system which serves user  
8 terminals via a plurality of ADSL (asymmetric digital subscriber line) modems.  
9 The apparatus comprises a switching unit having a first plurality of diverging  
10 ports connected to the switching system, a second plurality of diverging ports  
11 connected to the ADSL modems, and a plurality of converging ports adapted  
12 for connection to a plurality of internet lines, and a control unit for receiving a  
13 request signal of one of the user terminals and establishing in the switching  
14 unit a first set of branch connections between one of the first plurality of  
15 diverging ports and ones of the converging ports corresponding to the internet  
16 lines specified by the request signal and a second set of branch connections  
17 between one of the second plurality of diverging ports and the ones of the  
18 converging ports, the one of the first plurality of diverging ports being  
19 connected through a connection established in the switching system to one of  
20 the ADSL modems associated with the one user terminal from which the  
21 request signal is received.

22 According to a third aspect, the present invention provides a  
23 communication system comprising a public network switching system for  
24 establishing a connection between a first plurality of ports to which a plurality  
25 of user terminals are connected and a second plurality of ports in response to a

10 According to a fourth aspect, the present invention provides a method of  
11 communication for a public network switching system which serves user  
12 terminals by using a switching unit having a plurality of diverging ports  
13 connected to the switching system and a plurality of converging ports adapted  
14 for connection to a plurality of internet lines. The method comprises the steps  
15 of (a) receiving a request signal of one of the user terminals, (b) establishing in  
16 the switching system a connection between the one user terminal and one of  
17 the plurality of diverging ports in response to the request signal, (c)  
18 establishing in the switching system a plurality of connections in the public  
19 network switching system between ones of the plurality of converging ports  
20 and the plurality of internet lines according to phone numbers of internet  
21 service providers contained in the request signal, (d) establishing in the  
22 switching unit a set of branch connections between the one diverging port and  
23 the ones of the converging ports, and (e) repeating the steps (a), (b) and (d) by  
24 skipping the step (c) if connections are already established in the public  
25 network switching system.

### BRIEF DESCRIPTION OF THE DRAWINGS

The present invention will be described in further detail with reference to the accompanying drawings, in which:

Fig. 1 is a block diagram of a communication network incorporating a branch connection apparatus of the present invention;

Fig. 2 is a block diagram of the branch connection apparatus of Fig. 1;

Fig. 3 is a flowchart of the control unit of the branch connection apparatus;

Fig. 4 is a block diagram of a communication network in which the branch connection apparatus of this invention is combined with high speed interfaces such as asymmetric digital subscriber lines; and

Fig. 5 is a block diagram of the branch connection apparatus of Fig. 4.

### DETAILED DESCRIPTION

In Fig. 1, a communication network is illustrated as comprising a switch fabric 10 and a call processor 11 which together form an essential part of a PSTN (public switched telephone network) local switching office. Switch fabric 10 has a plurality of line ports  $L_{U1} \sim L_{UM}$  (or subscriber line interfaces) connected respectively to user terminals  $12_1 \sim 12_M$  and a plurality of trunk ports  $T_{P1} \sim T_{PN}$  (or trunk interfaces) respectively connected to the transmission lines of internet service providers  $13_1 \sim 13_N$ . For simplicity, the trunk ports are provided one for each internet service provider. More than one trunk port may be provided for each internet service provider.

According to the present invention, a branch connection apparatus 15 is provided. Branch connection apparatus 15 may be co-located with the switching system of the local switching office or located outside of the

1 switching office in an appropriate housing unit. Branch connection  
2 apparatus 15 includes a switching unit 16 and a control unit 17. Switching  
3 unit 16 has a plurality of diverging ports  $D_1 \sim D_M$  connected to trunk ports  $T_1$   
4  $\sim T_M$  of the switch fabric 10 and a plurality of converging ports  $C_1 \sim C_N$   
5 connected to line ports  $L_1 \sim L_N$  of the switch fabric 10. The converging ports  
6 of the switching unit 16 are provided in a one-to-one correspondence to the  
7 internet service providers  $13_1 \sim 13_N$ . If all user terminals 12 are subscribed to  
8 a flat rate service, all diverging ports of switching unit 16 correspond  
9 respectively to the user terminals  $12_1 \sim 12_M$ . Switching unit 16 has a  
10 dedicated input port connected via a control line 18 to a line port of the  
11 switch fabric 10 through which the control unit 16 communicates with the  
12 call processor 11 to set up connections in the switch fabric 10.

13 As shown in detail in Fig. 2, the switching unit 16 includes a plurality  
14 of line interface units 20-1 through 20-M for interfacing the trunk ports of  
15 switch fabric 10 to corresponding line ports of a switch fabric 22. Each line  
16 interface unit 20 represents the corresponding one of diverging ports  $D_1 \sim$   
17  $D_M$ . Switch fabric 22 has N sets of trunk ports with which a plurality of  
18 multiplexers/demultiplexers 23-1 through 23-N are associated respectively.  
19 Each of the multiplexers/demultiplexers has a number of input terminals  
20 connected to corresponding trunk ports of the associated set and one output  
21 terminal connected to a corresponding one of line interface units 24-1  $\sim$  24-N,  
22 which operate in compliance with communication protocols and  
23 transmission speeds of the user terminals. These line interface units are  
24 connected to line ports  $L_1 \sim L_N$  of the switch fabric 10 for interfacing to the  
25 internet service providers. Each multiplexer/demultiplexer 23 and

Control unit 17 includes a processor 30 and a number of memories 31 through 33 for storing ISP (internet service provider) phone numbers, user phone numbers, and user identifiers/passwords. Using the memories 31 through 33, the processor 30 determines whether the requesting user is a registered user. Processor 30 communicates with each internet service provider through the line interface units 24 to ascertain that the requesting user is to be allowed access to the Internet. Processor 30 uses a line interface unit 21 to supply a connection setup request to the control processor 11 via the control line 18 when establishing connections in the switch fabric 10.

When one of the user terminals desires to access the Internet, it sends a connection request packet. This packet is received by the call processor 11 of the PSTN switching system and a connection is established in the switch fabric 10 between the line terminal  $L_U$  of the calling user and one of the trunk ports  $T_1 \sim T_M$ . The request packet is passed on through the control line 18 to the line interface unit 21 of the switching unit 16, where it is communicated to the processor 30. The request packet from the calling user contains a number of destination (ISP) phone numbers and the phone number of the calling user terminal. These phone numbers are detected by the processor 30.

25 The operation of processor 30 proceeds according to a programmed

Sub  
pt



1 routine described in the flowchart of Fig. 3. When a call is received from a  
2 user terminal (step 41), the processor 30 proceeds to detect all phone numbers  
3 contained in the data received from the line interface 20 of the calling user  
4 terminal (step 42). At step 43, the phone number of the calling user is  
5 checked against phone numbers stored in the ISP phone number 31. If there is  
6 a match, if they mismatch with the stored ISP phone numbers, the processor  
7 30 recognizes that the request cannot accepted and terminates the routine.  
8 Otherwise, the processor advances to next decision step 44 to compare the  
9 phone number of the calling user with the phone numbers stored in the user  
10 phone number memory 32 to determine whether the calling user is  
11 authorized to gain access to the Internet.

12 If it is determined that the calling user is an authorized subscriber, the  
13 processor 30 proceeds from step 44 to step 45 to determine whether desired  
14 connections are already established in the switch fabric 10. If not, the  
15 processor 30 proceeds to step 46 to send a connection setup request to the call  
16 processor 11 to establish connections in the switch fabric 10 between line  
17 ports  $L_1 \sim L_N$  and trunk ports  $TP_1 \sim TP_N$ . The number of such connections is  
18 determined by the phone numbers contained in the user's connection request.  
19 At step 47, the processor 30 communicates through the line interface units 24  
20 to obtain call restriction data and compares the phone number of the calling  
21 user with the phone numbers contained in the restriction data. If there is a  
22 match, the processor 30 recognizes that the user is denied access to the  
23 Internet. Otherwise, the processor 30 recognizes that the user is allowed to  
24 access the Internet and proceeds to step 48 to control the switch fabric 22 to  
25 establish a set of branch connections between one of the diverging ports of the

AL  
CAX  
009020 "THE  
009020 "THE

AI Cont  
1 switching unit 16 and a number of converging ports determined by the phone  
2 numbers of internet service providers contained in the received packet.

3 If the decision at step 45 is affirmative, the processor 30 skips step 46  
4 With the connections established in both switch fabrics 10 and 22, the routine  
5 is then terminated.

6 If the decision at step 44 indicates that there is a mismatch between the  
7 calling user's phone number and the subscribed phone numbers, flow  
8 proceeds to step 49 to send a request packet to the calling user terminal via  
9 the associated line interface unit 20 to return a response containing a user's  
10 identifier (ID) and a user's password. If a response is returned (step 50), the  
11 processor 30 compares the data stored in the user ID/password memory 33  
12 (step 51). If a match is detected in step 51, the processor proceeds to step 45.  
13 Otherwise the routine is terminated.

14 It will be seen from the foregoing that, if the user terminal 12<sub>1</sub> initially  
15 sends a connection request packet to the network, requesting a set of N  
16 "branch connections" to internet service providers 13<sub>1</sub> ~ 13<sub>N</sub>. If the  
17 requesting user is authenticated, N paths are established in the switch fabric  
18 10 between line ports L<sub>1</sub> ~ L<sub>N</sub> and trunk ports T<sub>P1</sub> ~ T<sub>PN</sub> and a set of N branch  
19 connections is established in the switching unit 16 between the diverging port  
20 D<sub>1</sub> and the converging ports C<sub>1</sub> ~ C<sub>N</sub>, as indicated by thick dotted lines in Fig.  
21 1. If the user terminal 12<sub>2</sub> subsequently sends a connection, requesting an  
22 identical set of branch connections, and is then authenticated, a set of branch  
23 connections is established in the switch fabric 22. In the latter case, necessary  
24 connections are already established in the switch fabric 10. Thus, step 46 is  
25 skipped.

1 As a result,  $(2 \times N)$  paths are set up in the switching unit 16 and  $(2 + N)$   
2 paths are set up in the switch fabric 10 for the user terminals  $12_1$  and  $12_2$ . If  
3 these connections were established without using the branch connection  
4 apparatus 15,  $(2 \times N)$  paths must be established in the switch fabric 10. If  
5 there are  $M$  user terminals simultaneously requesting identical branch  
6 connections for  $N$  internet service providers,  $(M \times N)$  paths will be  
7 established in the switching unit 16 and  $(M + N)$  paths will be established in  
8 the switch fabric 10. Since in most cases the product  $(M \times N)$  is considerably  
9 greater than the sum  $(M + N)$ , the branch connection apparatus 15 can  
10 significantly relieve the switch fabric 10 of the burden of establishing  
11 "branch-connection" paths.

12 In addition, each of the transmission (access) lines between the switch  
13 fabric 10 and the internet service providers 13 is always lightly loaded with  
14 traffic. Therefore, the access line of each internet service provider can  
15 support the multiplexed traffic of a number of user terminals. Further, due to  
16 the significant increase in the utilization efficiency of the access lines, internet  
17 service providers are relieved of the burden of paying high access charges for  
18 providing flat rate services to internet subscribers.

19 In a modified embodiment, the converging ports of the branch  
20 connection apparatus 15 may be connected direct to the internet service  
21 providers.

22 Figs. 4 and 5 illustrate a modified embodiment of the present invention  
23 in which the end points of subscriber access lines are terminated with ADSL  
24 (asymmetric digital subscriber line) modems  $60_1 \sim 60_M$  and  $61_1 \sim 61_M$ . High  
25 speed signals from the ADSL modems  $61_1 \sim 61_M$  are connected by lines 62 to

1 converging ports  $AD_1 \sim AD_M$  of the switching unit 16 and their low speed  
2 signals such as speech signals are supplied to corresponding line ports of the  
3 switch fabric 10 for transmission over the Internet using a protocol known as  
4 VoIP (voice over IP). High speed signals at the diverging ports  $AD_1 \sim AD_M$   
5 are coupled through line interface units 70-1 ~ 70-M (Fig. 5) to line ports of  
6 the switch fabric 22.

7       If the user terminal  $12_2$  sends a connection request to the network,  
8 requesting a conference call, for example, and ADSL connections to different  
9 internet service providers, the call processor 11 establishes a connection 63 in  
10 the switch fabric 10 between the ADSL modem  $61_2$  and the diverging port  $D_2$   
11 of the switching unit 16. The connection request is passed on from the call  
12 processor 11 to the processor 30 via the control line 18. In response, the  
13 processor 30 requests the call processor 11 to establish connections 64 in the  
14 switch fabric 10 and then establishes a first set of branch connections between  
15 the diverging port  $D_2$  and the converging ports  $C_1 \sim C_N$  and a second set of  
16 branch connections between the diverging port  $AD_2$  and the converging ports  
17  $C_1 \sim C_N$ . The speech signal of user terminal  $12_2$  is split at the diverging port  
18  $D_2$  and the high speed signal of the user is split at the diverging port  $AD_2$ . At  
19 the converging ports  $C_1 \sim C_N$ , the split speech signals and the split high speed  
20 signals are multiplexed and transmitted to the IP network 13 through the  
21 connections 64.